

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** PUR-HS Mischlack diverse Farbtöne
- **Application of the substance / the preparation** *Lacquer*
- **Manufacturer/Supplier:**
MIPA AG
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **Further information obtainable from:** *Laboratory*
- **Information in case of emergency:** +49(0)700 24112112 (MIP)

2 Hazards identification

- **Hazard description:** *Not applicable.*
- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Has a narcotizing effect.
R 10 Flammable.
R 66 Repeated exposure may cause skin dryness or cracking.
R 67 Vapours may cause drowsiness and dizziness.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** *Mixture of substances listed below with nonhazardous additions.*

· **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1	<i>n</i> -butyl acetate R 10-66-67	10-25%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate ☒ Xi; R 10-36	2.5-10%
CAS: 112-07-2 EINECS: 203-933-3	2-butoxyethyl acetate ☒ Xn; R 20/21	≤ 2.5%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. ☒ Xn, ☒ Xi, ☒ N; R 10-37-51/53-65-66-67	≤ 2.5%
CAS: 97-86-9 EINECS: 202-613-0	isobutyl methacrylate ☒ Xi, ☒ N; R 10-36/37/38-43-50	≤ 2.5%

- **Additional information:** *For the wording of the listed risk phrases refer to section 16.*

4 First aid measures

- **After inhalation:** *Supply fresh air; consult doctor in case of complaints.*
- **After skin contact:** *Generally the product does not irritate the skin.*
- **After eye contact:** *Rinse opened eye for several minutes under running water.*

(Contd. on page 2)

Trade name: PUR-HS Mischlack diverse Farbtöne

(Contd. of page 1)

· **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Do not flush with water or aqueous cleansing agents

* 7 Handling and storage

- **Handling:**
- **Information for safe handling:** Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3

* 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

WEL ()	Short-term value: 966 mg/m ³ , 200 ppm
	Long-term value: 724 mg/m ³ , 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL ()	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk

112-07-2 2-butoxyethyl acetate

WEL ()	Short-term value: 50 ppm
	Long-term value: 20 ppm
	Sk

- **Additional information:** The lists valid during the making were used as basis.

- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Respiratory protection:** Not required.

(Contd. on page 3)

Trade name: PUR-HS Mischlack diverse Farbtöne

(Contd. of page 2)

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 124°C

· **Flash point:** 26°C (DIN 53213)

· **Ignition temperature:** 315°C (DIN 51794)

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 1.2 Vol %

Upper: 7.5 Vol %

· **Vapour pressure at 20°C:** 10.7 hPa

· **Density at 20°C:** 1.146 g/cm³ (DIN 53217)

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Viscosity:**

Kinematic at 20°C: 175 s (DIN 53211/4)

· **Solvent separation test:** < 3 %

· **Solvent content:**

Organic solvents: 28.4 %

VOC (EC) 325.6 g/l

(Contd. on page 4)

Printing date 21.08.2009

Revision: 21.08.2009

Trade name: PUR-HS Mischlack diverse Farbtöne

(Contd. of page 3)

· Solids content (weight-%): 71.6 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous decomposition products:** Carbon monoxide

11 Toxicological information· **Acute toxicity:**· **LD/LC50 values relevant for classification:****64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral LD50 >6800 mg/kg (rat)

Dermal LD50 >3400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

· **Primary irritant effect:**

- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

12 Ecological information· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations· **Product:**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.**14 Transport information**· **Land transport ADR/RID (cross-border)**· **ADR/RID class:** 3 (F1) Flammable liquids.· **Danger code (Kemler):** 30

(Contd. on page 5)

Trade name: PUR-HS Mischlack diverse Farbtöne

(Contd. of page 4)

- **UN-Number:** 1263
- **Packaging group:** III
- **Hazard label:** 3
- **Description of goods:** 1263 PAINT, special provision 640E
- **Remarks:** ≤ 450 l: -

· **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1263
- **Label:** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** PAINT
- **Remarks:** ≤ 30 l: -

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1263
- **Label:** 3
- **Packaging group:** III
- **Proper shipping name:** PAINT

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Risk phrases:**

- 10 Flammable.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

- 2 Keep out of the reach of children.
- 25 Avoid contact with eyes.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 46 If swallowed, seek medical advice immediately and show this container or label.

· **Special labelling of certain preparations:**

Contains isobutyl methacrylate. May produce an allergic reaction.

· **National regulations:**

· **Information about limitation of use:**

112-07-2	2-butoxyethyl acetate	4
111-76-2	2-butoxyethanol	4

(Contd. on page 6)

Printing date 21.08.2009

Revision: 21.08.2009

Trade name: PUR-HS Mischlack diverse Farbtöne

(Contd. of page 5)

Class	Share in %
NK	25-50

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

- 10 Flammable.
- 20/21 Harmful by inhalation and in contact with skin.
- 36 Irritating to eyes.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 37 Irritating to respiratory system.
- 43 May cause sensitisation by skin contact.
- 50 Very toxic to aquatic organisms.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** MIPA AG, Abteilung Umweltschutz

· **Contact:** Michaela Knall

· *** Data compared to the previous version altered.**